

MODEL 38XX Series

VXI DMM & M-Modules



6.5 Digit DMM

Features & Benefits

- Dynamic Range: +/-3,300,000 Counts.
- Isolation: +/-350V to Chassis.
- Construction: Shielded Module.
- >110dB CMRR.
- >95dB Line Rejection.
- All Inputs and Outputs Protected for:
 - Over Voltage Events
 - Source Short Circuits
 - Over Current
 - ESD
 - Noise (Common Mode)
- 33VDC range is significant in testing Automotive 12V & 24V systems.
- One Million Hours MTBF.
- No Manual Adjustments Needed.

ASCOR Model 3801 VXI DMM With M-Module Capability ASCOR Model 3802 VXI DMM Without M-Module Capability

The ASCOR Model 3801 is a one wide, C-size VXI card which comes standard with a Digital Multimeter (DMM) and the capability of adding an industry standard M-Module mezzanine card.

The Model 3802 is the same as the Model 3801 except does not have the M-Module capability.

The on-board 6.5 digit DMM is a high performance Digital Multimeter optimized for a variety of applications such as the following:

- ATE flight line test systems
- Automated production testing
- Control and data acquisition
- Portable field testing
- Laboratory automation
- Disk drive testing
- Resistance network testing
- Semiconductor Parametric testing
- Cable & Connector testers
- Automotive test systems

There are two types of DMMs available with the Model 38XX. The standard DMM (3801-1004 or 3802-1004) provides the following measurement capabilities:

- DC Volts and Current
 - AC Volts and Current
 - Resistance (2-Wire and 4-Wire)
- Each function provides at least four ranges of values. Accuracy on the DC Volts and on the Resistance functions is better than 0.0004%.

The extended capability DMM/LCR (3801-1005 or 3802-1005) provides for all the functions listed above for the standard DMM. In addition the DMM/LCR provides the following additional capabilities:

- Resistance (6-Wire Guarded)
- Temperature (-150°C to +650°C)
- Leakage Current (1nA to 3300nA)
- Capacitance (1nF to 10 mF)
- Inductance (1uH to 3.3H)
- Peak to Peak, Crest & Median (Volts)
- Timing Functions
- Sourcing AC/DC:
 - DCV Source: (-10.0V to +10.0V)
 - ACV Source: (0v to 20V P to P)
 - DC Current: (1.25uA to 12.5mA)

M-Modules Available

The 3801 also has the capability of mounting a single industry standard M-Module mezzanine card. These units provide functions such as:

- Analog/Digital Conversion (A/D)
 - Digital/Analog Conversion (D/A)
 - Universal Timer/Counter (UTC)
- Any industry standard M-Module may be used. M-Modules provided by ASCOR come complete with a software driver provided. Other M-Modules not provided by ASCOR Inc. will require the user to provide their own software driver.

As with all ASCOR VXI Modules, The Model 3801 is a register-based device. The software drivers that are provided were developed using LabWindows/CVI and are written in C++.



Custom Solutions Through Engineering Innovation

4384 Enterprise Place, Fremont, CA 94538-6365
Telephone: (510)490-2300
Fax: (510)490-8493
Website: www.ascor-inc.com


MODEL 38XX

ASCOR Model 3801 VXI DMM
With M-Module

ASCOR Model 3802 VXI DMM
Without M-Module Capability


Time Measurement Functions

- Duty Cycle: 0% to 100%
- Period: 3 μ s to 1s
- Frequency: 1Hz to 300KHz



Special AC Measurements

- Median (1005)
 - Measures AC Signal Bias Level
 - Signal Quality Indicator
 - Defines Threshold Level For:
 - Counter, Pulse Width, Duty Cycle, Event Center



Custom Solutions Through Engineering Innovation

ASCOR, founded in 1987 and headquartered in California's Silicon Valley, provides a complete line of VXI Switching and Digital Modules for industrial, medical, scientific and governmental automatic test applications. Ascort VXI products are the quietest, cleanest, highest density VXI modules commercially available.



Custom Solutions Through Engineering Innovation

4384 Enterprise Place, Fremont, CA 94538-6365
Telephone: (510)490-2300
Fax: (510)490-8493
Website: www.ascor-inc.com

Model 3801-1004 or 3802-1004 Digital MultiMeter (DMM) for VXI

DC Volts

- 100nV Resolution
- 4 ranges (330mV, 3.3V, 33V, 330V)
- Accuracy is better than 0.004%

DC Current

- 10nA Resolution
- 4 ranges (3.3mA, 33mA, 330mA, 2.5A)
- Accuracy is better than 0.1%

AC Volts (RMS)

- 100nV Resolution
- 4 ranges (330mV, 3.3V, 33V, 250V)
- Accuracy is better than 0.9% (20 Hz to 50 KHz)

AC Current (RMS)

- 1nA Resolution
- 4 ranges (3.3mA, 33mA, 330mA, 2.5A)
- Accuracy is better than 0.9% (20 Hz to 50 KHz)

Resistance (Two Wire)

- 10u ohms Resolution
- 5 ranges (330 ohms, 3.3 Kohms, 33 Kohms, 330 Kohms, 3.3 Mohms)
- Accuracy is better than 0.003%

Resistance (Four Wire)

- 10u ohms Resolution
- 4 ranges (330 ohms, 3.3 Kohms, 33 Kohms, 330 Kohms)
- Accuracy is better than 0.003%

Model 3801-1005 or 3802-1005 Digital MultiMeter (DMM) for VXI

DC Volts

- 100nV Resolution
- 4 ranges (330mV, 3.3V, 33V, 330V)
- Accuracy is better than 0.004%

DC Current

- 10nA Resolution
- 4 ranges (3.3mA, 33mA, 330mA, 2.5A)
- Accuracy is better than 0.1%

AC Volts (RMS)

- 100nV Resolution
- 4 ranges (330mV, 3.3V, 33V, 250V)
- Accuracy is better than 0.9% (20 Hz to 50 KHz)

AC Current (RMS)

- 1nA Resolution
- 4 ranges (3.3mA, 33mA, 330mA, 2.5A)
- Accuracy is better than 0.9% (20 Hz to 50 KHz)

Resistance (Two Wire)

- 10u ohms Resolution
- 8 ranges (33 ohms, 330 ohm, 3.3 Kohms, 33 Kohms, 330 Kohms, 3.3 Mohms, 33 Mohms, 330 Mohms)
- Accuracy is better than 0.003%

Resistance (Four Wire)

- 10u ohms Resolution
- 8 ranges (33 ohms, 330 ohm, 3.3 Kohms, 33 Kohms, 330 Kohms, 3.3 Mohms, 33 Mohms, 330 Mohms)
- Accuracy is better than 0.003%

Resistance (Six Wire Guarded)

- 5 ranges (33 ohms, 330 ohm, 3.3 Kohms, 33 Kohms, 330 Kohms)
- Accuracy is better than 0.03%

Temperature

- 0.01° C Resolution
- Range is -150° C to 650° C
- Accuracy and Range depend on RTD Type
- The internal temperature of the 1005 can also be monitored

Leakage

- 3 Ranges (100 nA, 1000nA, 3300nA)
- Accuracy is better than 2.0%

Capacitance

- 7 Ranges (10nF, 100nF, 1uF, 10uF, 100uF, 1mF, 10mF)
- Accuracy is better than 2% .

Inductance

- 6 Ranges (33uH, 330uH, 3.3mH, 33mH, 330mH, 3.3H)

Peak to Peak, Crest, and Median

- 4 Ranges (330mV, 3.3V, 33V, 250V)
- Accuracy is better than 1.5%

Timing Functions

- Timing Functions (5 available)
 - ACV Frequency & Period
 - ACI Frequency & Period
 - Duty Cycle Measurement
 - Pulse Width
 - Totalizer

AC/DC Voltage Source and Current Source

- DC Voltage Source: (-10.0V TO +10.0v)
Accuracy is better than 0.13%
- AC Voltage Source: (0 to 20 V Peak to Peak)
Accuracy is better than 0.8%.
- DC Current Source: 5 Ranges (1.25uA, 12.5uA, 125uA, 1.25mA, 12.5mA)
Accuracy is better than 0.2%